

The makerobust package

Heiko Oberdiek*

<heiko.oberdiek at gmail.com>

2016/05/16 v1.1

Abstract

Package `makerobust` provides `\MakeRobustCommand` that converts an existing macro to a robust one.

Contents

1	User interface	1
1.1	Example	2
2	Implementation	2
3	Installation	3
3.1	Download	3
3.2	Bundle installation	3
3.3	Package installation	4
3.4	Refresh file name databases	4
3.5	Some details for the interested	4
4	Catalogue	5
5	History	5
	[2006/03/18 v1.0]	5
	[2016/05/16 v1.1]	5
6	Index	6

1 User interface

L^AT_EX offers `\DeclareRobustCommand` to define a robust macro that does not break if it is used in moving arguments. Sometimes a macro is already defined, but not robust. For example, `\(` and `\)` are not robust, inside `\section` the user must use `\protect` explicitly. This could be avoided by making `\(` and `\)` robust.

`\MakeRobustCommand{\<cmd>}`

`\MakeRobustCommand` redefines the macro `\<cmd>` by using `\DeclareRobustCommand` and the existing definition of the macro `\<cmd>`.

*Please report any issues at <https://github.com/ho-tex/oberdiek/issues>

- It is an error if $\langle cmd \rangle$ is undefined. If you want to define a robust command, then you can use `\DeclareRobustCommand` directly.
- If the macro has previously been defined by `\DeclareRobustCommand` then the redefinition of `\MakeRobustCommand` is omitted, because the macro is already robust. Only an information entry is written to the `.log` file. Thus you do not get a warning or an error if the macro is already robust because of an updated LaTeX or package that defines the macro.
- Two macros are defined for a macro, defined by `\DeclareRobustCommand`. Example:

```
\DeclareRobustCommand{\foobar}{definition text}
```

Then the macro “`\foobar`” contains the protection code and, depending on the protection mode, calls the internal macro “`\foobar` ”. Notice the space at the end of the macro name. This internal macro “`\foobar` ” now contains the definition “`definition text`”, given in `\DeclareRobustCommand`.

Sometimes it can happen, that the internal macro already exists. This can be caused by a previous `\DeclareRobustCommand` followed by `\renewcommand`. Then the redefinition by `\MakeRobustCommand` would be safe.

However, it can also be possible that the macro is already robust, using the internal macro, but with a different protection code. The redefinition by `\MakeRobustCommand` would then generate an infinite loop.

Therefore `\MakeRobustCommand` raises an error message, if the internal macro (with space at the end) already exists.

1.1 Example

```
1 \example
2 \documentclass{article}
3 \usepackage{makerobust}
4 \MakeRobustCommand\
5 \MakeRobustCommand\
6 \pagestyle{headings}
7 \begin{document}
8 \tableofcontents
9 \section{Einstein:  $(E=mc^2)$ }
10 \newpage
11 Second page.
12 \end{document}
13 \example
```

2 Implementation

```
14 \package
15 \NeedsTeXFormat{LaTeX2e}
16 \ProvidesPackage{makerobust}%
17 [2016/05/16 v1.1 Make existing macro robust (HO)]%
18 \def\MakeRobustCommand#1{%
19   \begingroup
20   \@ifundefined{\expandafter\@gobble\string#1}{%
21     \endgroup
22     \PackageError{makerobust}{%
23       Macro \string'\string#1\string' is not defined%
24     }\@ehc
```

```

25 }{%
26   \global\let\MR@temp#1%
27   \let#1\@undefined
28   \expandafter\let\expandafter\MR@temp
29     \csname\expandafter\@gobble\string#1 \endcsname
30   \DeclareRobustCommand#1{%
31     \ifx#1\MR@temp
32       \endgroup
33       \PackageInfo{makerobust}{%
34         \string'\string#1\string' is already robust%
35       }%
36     \else
37       \@ifundefined{MR@temp}{%
38         \global\let\MR@temp#1%
39         \endgroup
40         \expandafter\let\csname\expandafter\@gobble\string#1 \endcsname#1%
41         \let#1\MR@temp
42       }{%
43         \endgroup
44         \PackageError{makerobust}{%
45           Internal macro \string'\string#1 \string' already exists%
46         }\@ehc
47       }%
48     \fi
49   }%
50 }
51 </package>

```

3 Installation

3.1 Download

Package. This package is available on CTAN¹:

[CTAN:macros/latex/contrib/oberdiek/makerobust.dtx](#) The source file.

[CTAN:macros/latex/contrib/oberdiek/makerobust.pdf](#) Documentation.

Bundle. All the packages of the bundle ‘oberdiek’ are also available in a TDS compliant ZIP archive. There the packages are already unpacked and the documentation files are generated. The files and directories obey the TDS standard.

[CTAN:install/macros/latex/contrib/oberdiek.tds.zip](#)

TDS refers to the standard “A Directory Structure for T_EX Files” ([CTAN:tds/tds.pdf](#)). Directories with `texmf` in their name are usually organized this way.

3.2 Bundle installation

Unpacking. Unpack the `oberdiek.tds.zip` in the TDS tree (also known as `texmf` tree) of your choice. Example (linux):

```
unzip oberdiek.tds.zip -d ~/texmf
```

¹<http://ctan.org/pkg/makerobust>

Script installation. Check the directory `TDS:scripts/oberdiek/` for scripts that need further installation steps. Package `attachfile2` comes with the Perl script `pdfatfi.pl` that should be installed in such a way that it can be called as `pdfatfi`. Example (linux):

```
chmod +x scripts/oberdiek/pdfatfi.pl
cp scripts/oberdiek/pdfatfi.pl /usr/local/bin/
```

3.3 Package installation

Unpacking. The `.dtx` file is a self-extracting `docstrip` archive. The files are extracted by running the `.dtx` through plain \TeX :

```
tex makerobust.dtx
```

TDS. Now the different files must be moved into the different directories in your installation TDS tree (also known as `texmf` tree):

<code>makerobust.sty</code>	\rightarrow <code>tex/latex/oberdiek/makerobust.sty</code>
<code>makerobust.pdf</code>	\rightarrow <code>doc/latex/oberdiek/makerobust.pdf</code>
<code>makerobust-example.tex</code>	\rightarrow <code>doc/latex/oberdiek/makerobust-example.tex</code>
<code>makerobust.dtx</code>	\rightarrow <code>source/latex/oberdiek/makerobust.dtx</code>

If you have a `docstrip.cfg` that configures and enables `docstrip`'s TDS installing feature, then some files can already be in the right place, see the documentation of `docstrip`.

3.4 Refresh file name databases

If your \TeX distribution (`te \TeX` , `mik \TeX` , ...) relies on file name databases, you must refresh these. For example, `te \TeX` users run `texhash` or `mktexlsr`.

3.5 Some details for the interested

Attached source. The PDF documentation on CTAN also includes the `.dtx` source file. It can be extracted by AcrobatReader 6 or higher. Another option is `pdftk`, e.g. unpack the file into the current directory:

```
pdftk makerobust.pdf unpack_files output .
```

Unpacking with \LaTeX . The `.dtx` chooses its action depending on the format:

plain \TeX : Run `docstrip` and extract the files.

\LaTeX : Generate the documentation.

If you insist on using \LaTeX for `docstrip` (really, `docstrip` does not need \LaTeX), then inform the autodetect routine about your intention:

```
latex \let\install=y\input{makerobust.dtx}
```

Do not forget to quote the argument according to the demands of your shell.

Generating the documentation. You can use both the `.dtx` or the `.drv` to generate the documentation. The process can be configured by the configuration file `ltxdoc.cfg`. For instance, put this line into this file, if you want to have A4 as paper format:

```
\PassOptionsToClass{a4paper}{article}
```

An example follows how to generate the documentation with pdfL^AT_EX:

```
pdflatex makerobust.dtx
makeindex -s gind.ist makerobust.idx
pdflatex makerobust.dtx
makeindex -s gind.ist makerobust.idx
pdflatex makerobust.dtx
```

4 Catalogue

The following XML file can be used as source for the [T_EX Catalogue](#). The elements `caption` and `description` are imported from the original XML file from the Catalogue. The name of the XML file in the Catalogue is `makerobust.xml`.

```
52 (*catalogue)
53 <?xml version='1.0' encoding='us-ascii'?>
54 <!DOCTYPE entry SYSTEM 'catalogue.dtd'>
55 <entry datestamp='$Date$' modifier='$Author$' id='makerobust'>
56   <name>makerobust</name>
57   <caption>Making a macro robust.</caption>
58   <authorref id='auth:oberdiek' />
59   <copyright owner='Heiko Oberdiek' year='2006' />
60   <license type='lppl1.3' />
61   <version number='1.1' />
62   <description>
63     This package provides the command MakeRobustCommand
64     that converts an existing macro to a robust one.
65   <p/>
66   The package is part of the <xref refid='oberdiek'>oberdiek</xref>
67   bundle.
68 </description>
69 <documentation details='Package documentation'
70   href='ctan:/macros/latex/contrib/oberdiek/makerobust.pdf' />
71 <ctan file='true' path='/macros/latex/contrib/oberdiek/makerobust.dtx' />
72 <miktex location='oberdiek' />
73 <texlive location='oberdiek' />
74 <install path='/macros/latex/contrib/oberdiek/oberdiek.tds.zip' />
75 </entry>
76 </catalogue>
```

5 History

[2006/03/18 v1.0]

- First version.

[2016/05/16 v1.1]

- Documentation updates.

6 Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; plain numbers refer to the code lines where the entry is used.

Symbols		M	
\(4, 9	\MakeRobustCommand	<i>1</i> , 4, 5, 18
\)	5, 9	\MR@gtemp	26, 31, 38, 41
\@ehc	24, 46	\MR@temp	28
\@gobble	20, 29, 40		
\@ifundefined	20, 37	N	
\@undefined	27	\NeedsTeXFormat	15
		\newpage	10
B		P	
\begin	7	\PackageError	22, 44
C		\PackageInfo	33
\csname	29, 40	\pagestyle	6
D		\ProvidesPackage	16
\DeclareRobustCommand	30	S	
\documentclass	2	\section	9
E		T	
\end	12	\tableofcontents	8
\endcsname	29, 40	U	
I		\usepackage	3
\ifx	31		