

libyui-mga-qt
1.0.3

Generated by Doxygen 1.8.12

Contents

1	Hierarchical Index	1
1.1	Class Hierarchy	1
2	Class Index	3
2.1	Class List	3
3	Class Documentation	5
3.1	YMGA_QCBTable::Private Struct Reference	5
3.1.1	Detailed Description	5
3.2	YMGA_QCBTable Class Reference	5
3.2.1	Detailed Description	7
3.2.2	Member Function Documentation	7
3.2.2.1	addItem()	7
3.2.2.2	addItem()	8
3.2.2.3	cellChanged()	8
3.2.2.4	checkItem()	9
3.2.2.5	deleteAllItems()	9
3.2.2.6	deselectAllItems()	9
3.2.2.7	preferredHeight()	9
3.2.2.8	preferredWidth()	10
3.2.2.9	selectItem()	10
3.2.2.10	setEnabled()	10

3.2.2.11	setKeepSorting()	11
3.2.2.12	setKeyboardFocus()	11
3.2.2.13	setSize()	11
3.2.2.14	slotContextMenu	11
3.3	YMGA_QCTableListViewItem Class Reference	12
3.3.1	Detailed Description	13
3.4	YMGAQWidgetFactory Class Reference	13
3.4.1	Detailed Description	14
3.4.2	Constructor & Destructor Documentation	14
3.4.2.1	YMGAQWidgetFactory()	14
3.5	YQWE Class Reference	15
3.5.1	Detailed Description	15
Index		17

Chapter 1

Hierarchical Index

1.1 Class Hierarchy

This inheritance list is sorted roughly, but not completely, alphabetically:

YMGA_QCBTable::Private	5
QFrame	
YMGA_QCBTable	5
QY2ListViewItem	
YMGA_QCBTableListViewItem	12
YExternalWidgets	
YQWE	15
YMGA_CBTable	
YMGA_QCBTable	5
YMGAWidgetFactory	
YMGAWidgetFactory	13

Chapter 2

Class Index

2.1 Class List

Here are the classes, structs, unions and interfaces with brief descriptions:

YMGA_QCBTable::Private	5
YMGA_QCBTable	5
YMGA_QCBTableListViewItem	
Visual representation of a YCBTableItem	12
YMGAQWidgetFactory	
Concrete widget factory for mandatory widgets	13
YQWE	15

Chapter 3

Class Documentation

3.1 YMGA_QCBBTable::Private Struct Reference

Public Attributes

- unsigned int [firstColumnOffset](#)
< offset to first YCell usually 1 if checkbox Enabled and mode is YCBBTableCheckBoxOnFirstColumn 0 otherwise

3.1.1 Detailed Description


Definition at line [42](#) of file [YMGA_QCBBTable.cc](#).

The documentation for this struct was generated from the following file:


- [/home/iurt/rpmbuild/BUILD/libyui-mga-qt-1.0.3/src/YMGA_QCBBTable.cc](#)

3.2 YMGA_QCBBTable Class Reference

Inheritance diagram for YMGA_QCBBTable:



Collaboration diagram for YMGA_QCBBTable:



Classes

- struct [Private](#)

Public Member Functions

- [YMGA_QCBBTable](#) (YWidget *parent, YTableHeader *header, YCBBTableMode checkBoxMode)
Constructor.
- virtual [~YMGA_QCBBTable](#) ()
Destructor.
- virtual void [setKeepSorting](#) (bool keepSorting)
Switch between sorting by item insertion order (keepSorting: true) or allowing the user to sort by an arbitrary column (by clicking on the column header).
- virtual void [addItem](#) (YItem *item)
Add an item.
- virtual void [addItem](#) (const YItemCollection &itemCollection)
Add multiple items.
- virtual void [selectItem](#) (YItem *item, bool selected=true)
Select or deselect an item.
- virtual void [deselectAllItems](#) ()
Deselect all items.
- virtual void [deleteAllItems](#) ()
Delete all items.
- virtual void [cellChanged](#) (const YTableCell *cell)
Notification that a cell (its text and/or its icon) was changed from the outside.
- void [checkItem](#) (YItem *item, bool checked=true)
check/uncheck Item from application.
- virtual void [setEnabled](#) (bool enabled)
Set enabled/disabled state.
- virtual int [preferredWidth](#) ()
Preferred width of the widget.

- virtual int [preferredHeight](#) ()
Preferred height of the widget.
- virtual void [setSize](#) (int newWidth, int newHeight)
Set the new size of the widget.
- virtual bool [setKeyboardFocus](#) ()
Accept the keyboard focus.
- int [checkboxItemColumn](#) ()
returns which column is managed by checkboxes, if any -1 otherwise

Protected Slots

- void [slotSelected](#) (QTreeWidgetItem *)
Notification that an item is selected (single click or keyboard).
- void [slotActivated](#) (QTreeWidgetItem *listViewItem, int column)
Notification that an item is activated (double click or keyboard).
- void [slotContextMenu](#) (const QPoint &pos)
Propagate a context menu selection.
- void [slotcolumnClicked](#) (QTreeWidgetItem *item, int col)

Protected Member Functions

- void [selectOrigItem](#) (QTreeWidgetItem *listViewItem)
Select the original item (the YCBTableItem) that corresponds to the specified listViewItem.
- void [addItem](#) (YItem *item, bool batchMode, bool resizeColumnsToContent)
Internal [addItem\(\)](#) method that will not do expensive operations in batch mode.

Protected Attributes

- QY2ListView * [_qt_listView](#)

3.2.1 Detailed Description

Definition at line 38 of file [YMGA_QCBTable.h](#).

3.2.2 Member Function Documentation

3.2.2.1 addItem()

```
void YMGA_QCBTable::addItem (
    YItem * item ) [virtual]
```

Add an item.

Reimplemented from YSelectionWidget.

Definition at line 143 of file [YMGA_QCBTable.cc](#).

3.2.2.2 addItem()


```
void YMGA_QCTable::addItem (
    const YItemCollection & itemCollection ) [virtual]
```

Add multiple items.

Reimplemented for efficiency from YSelectionWidget.

Definition at line 207 of file [YMGA_QCTable.cc](#).

Here is the call graph for this function:



3.2.2.3 cellChanged()

```
void YMGA_QCTable::cellChanged (
    const YTableCell * cell ) [virtual]
```


Notification that a cell (its text and/or its icon) was changed from the outside.

Applications are required to call this whenever a table cell is changed after adding the corresponding table item (the row) to the table widget.

Reimplemented from YTable.

Definition at line 291 of file [YMGA_QCTable.cc](#).

Here is the call graph for this function:



3.2.2.4 checkItem()

```
void YMGA_QCBTable::checkItem (
    YItem * item,
    bool checked = true )
```

check/uncheck Item from application.

Note that item->check(true) does not update the table

Definition at line 257 of file [YMGA_QCBTable.cc](#).

Here is the call graph for this function:



3.2.2.5 deleteAllItems()

```
void YMGA_QCBTable::deleteAllItems ( ) [virtual]
```

Delete all items.

Reimplemented from YSelectionWidget.

Definition at line 283 of file [YMGA_QCBTable.cc](#).

3.2.2.6 deselectAllItems()

```
void YMGA_QCBTable::deselectAllItems ( ) [virtual]
```

Deselect all items.

Reimplemented from YSelectionWidget.

Definition at line 273 of file [YMGA_QCBTable.cc](#).

3.2.2.7 preferredHeight()

```
int YMGA_QCBTable::preferredHeight ( ) [virtual]
```

Preferred height of the widget.

Reimplemented from YWidget.

Definition at line 399 of file [YMGA_QCBTable.cc](#).

3.2.2.8 preferredWidth()

```
int YMGA_QCBTable::preferredWidth ( ) [virtual]
```

Preferred width of the widget.

Reimplemented from YWidget.

Definition at line 389 of file [YMGA_QCBTable.cc](#).

3.2.2.9 selectItem()


```
void YMGA_QCBTable::selectItem (
    YItem * item,
    bool selected = true ) [virtual]
```

Select or deselect an item.

Reimplemented from YSelectionWidget.

Definition at line 233 of file [YMGA_QCBTable.cc](#).

Here is the call graph for this function:



3.2.2.10 setEnabled()

```
void YMGA_QCBTable::setEnabled (
    bool enabled ) [virtual]
```

Set enabled/disabled state.

Reimplemented from YWidget.

Definition at line 379 of file [YMGA_QCBTable.cc](#).

3.2.2.11 setKeepSorting()

```
void YMGA_QCBTable::setKeepSorting (
    bool keepSorting ) [virtual]
```

Switch between sorting by item insertion order (keepSorting: true) or allowing the user to sort by an arbitrary column (by clicking on the column header).

Reimplemented from YTable.

Definition at line 134 of file [YMGA_QCBTable.cc](#).

3.2.2.12 setKeyboardFocus()

```
bool YMGA_QCBTable::setKeyboardFocus ( ) [virtual]
```

Accept the keyboard focus.

Reimplemented from YWidget.

Definition at line 416 of file [YMGA_QCBTable.cc](#).

3.2.2.13 setSize()

```
void YMGA_QCBTable::setSize (
    int newWidth,
    int newHeight ) [virtual]
```

Set the new size of the widget.

Reimplemented from YWidget.

Definition at line 409 of file [YMGA_QCBTable.cc](#).

3.2.2.14 slotContextMenu

```
void YMGA_QCBTable::slotContextMenu (
    const QPoint & pos ) [protected], [slot]
```

Propagate a context menu selection.

This will trigger an 'ContextMenuActivated' event if 'notifyContextMenu' is set.

Definition at line 425 of file [YMGA_QCBTable.cc](#).

The documentation for this class was generated from the following files:


- [/home/iurt/rpmbuild/BUILD/libyui-mga-qt-1.0.3/src/YMGA_QCBTable.h](#)
- [/home/iurt/rpmbuild/BUILD/libyui-mga-qt-1.0.3/src/YMGA_QCBTable.cc](#)

3.3 YMGA_QCBBTableListItem Class Reference


Visual representation of a YCBBTableItem.

```
#include <YMGA_QCBBTable.h>
```

Inheritance diagram for YMGA_QCBBTableListItem:



Collaboration diagram for YMGA_QCBBTableListItem:



Public Member Functions

- [YMGA_QCBBTableListItem](#) ([YMGA_QCBBTable](#) *table, [QY2ListView](#) *parent, [YCBBTableItem](#) *origItem)
Constructor.
- [YMGA_QCBBTable](#) * table () const

Return the parent table widget.

- YCBTableItem * [origItem](#) () const

Return the corresponding YCBTableItem.

- void [updateCell](#) (const YTableCell *cell)

Update this item's display with the content of 'cell'.

Protected Attributes

- [YMGA_QCBTable](#) * **_table**
- YCBTableItem * **_origItem**

3.3.1 Detailed Description

Visual representation of a YCBTableItem.

Definition at line [212](#) of file [YMGA_QCBTable.h](#).

The documentation for this class was generated from the following files:


- /home/iurt/rpmbuild/BUILD/libyui-mga-qt-1.0.3/src/YMGA_QCBTable.h
- /home/iurt/rpmbuild/BUILD/libyui-mga-qt-1.0.3/src/YMGA_QCBTable.cc

3.4 YMGAQWidgetFactory Class Reference


Concrete widget factory for mandatory widgets.

```
#include <YMGAQWidgetFactory.h>
```

Inheritance diagram for YMGAQWidgetFactory:



Collaboration diagram for YMGAQWidgetFactory:



Public Member Functions

- virtual YMGA_CBTable * **createCBTable** (YWidget *parent, YTableHeader *header_disown, YCBTableMode mode=YCBTableCheckBoxOnFirstColumn)

Protected Member Functions

- [YMGAQWidgetFactory](#) ()
Constructor.
- virtual [~YMGAQWidgetFactory](#) ()
Destructor.

Friends

- class **YQWE**

3.4.1 Detailed Description

Concrete widget factory for mandatory widgets.

Definition at line 40 of file [YMGAQWidgetFactory.h](#).

3.4.2 Constructor & Destructor Documentation

3.4.2.1 YMGAQWidgetFactory()

```
YMGAQWidgetFactory::YMGAQWidgetFactory ( ) [protected]
```

Constructor.

Use YUI::widgetFactory() to get the singleton for this class.


Definition at line 43 of file [YMGAQWidgetFactory.cc](#).

The documentation for this class was generated from the following files:


- /home/iurt/rpmbuild/BUILD/libyui-mga-qt-1.0.3/src/YMGAQWidgetFactory.h
- /home/iurt/rpmbuild/BUILD/libyui-mga-qt-1.0.3/src/YMGAQWidgetFactory.cc

3.5 YQWE Class Reference

Inheritance diagram for YQWE:



Collaboration diagram for YQWE:



Public Member Functions

- **YQWE** (const std::string &name)

Protected Member Functions

- virtual YExternalWidgetFactory * **createExternalWidgetFactory** ()

3.5.1 Detailed Description

Definition at line 29 of file [YQWE.h](#).

The documentation for this class was generated from the following files:

- /home/iurt/rpmbuild/BUILD/libyui-mga-qt-1.0.3/src/YQWE.h
- /home/iurt/rpmbuild/BUILD/libyui-mga-qt-1.0.3/src/YQWE.cc

Index

- addItem
 - YMGA_QCBBTable, [7](#)
- addItem
 - YMGA_QCBBTable, [7](#)
- cellChanged
 - YMGA_QCBBTable, [8](#)
- checkItem
 - YMGA_QCBBTable, [8](#)
- deleteAllItems
 - YMGA_QCBBTable, [9](#)
- deselectAllItems
 - YMGA_QCBBTable, [9](#)
- preferredHeight
 - YMGA_QCBBTable, [9](#)
- preferredWidth
 - YMGA_QCBBTable, [9](#)
- selectItem
 - YMGA_QCBBTable, [10](#)
- setEnabled
 - YMGA_QCBBTable, [10](#)
- setKeepSorting
 - YMGA_QCBBTable, [10](#)
- setKeyboardFocus
 - YMGA_QCBBTable, [11](#)
- setSize
 - YMGA_QCBBTable, [11](#)
- slotContextMenu
 - YMGA_QCBBTable, [11](#)
- YMGA_QCBBTable, [5](#)
 - addItem, [7](#)
 - addItem, [7](#)
 - cellChanged, [8](#)
 - checkItem, [8](#)
 - deleteAllItems, [9](#)
 - deselectAllItems, [9](#)
 - preferredHeight, [9](#)
 - preferredWidth, [9](#)
 - selectItem, [10](#)
 - setEnabled, [10](#)
 - setKeepSorting, [10](#)
 - setKeyboardFocus, [11](#)
 - setSize, [11](#)
 - slotContextMenu, [11](#)
 - YMGA_QCBBTable::Private, [5](#)
 - YMGA_QCBBTableListViewItem, [12](#)
 - YMQAQWidgetFactory, [13](#)
 - YMQAQWidgetFactory, [14](#)
 - YQWE, [15](#)